



MORBARK®



MADE FOR **MORE** TO KEEP PACE WITH **YOU**

STATIONARY CHIPPER

The **Stationary Chipper** is designed for chipping sawmill waste, slabs, edgings and roundwood for pulp and paper as well as other markets. Morbark stationary chippers produce quality dimensional chips in sizes ranging from 0.5" (1.3 cm) to 2" (5.1 cm) in length. Wear parts are easily replaced and readily available, keeping maintenance and downtime to a minimum. Precision manufacturing techniques ensure optimum chip quality, even in two- and three-knife chippers. A variety of discharge configurations, leg packages, feed systems and customized bases are available.

OPTIONS INCLUDE

- 6 steel chipper support legs to accommodate 60" (152.4 cm) elevation to bottom of infeed spout
- Transition piece for 48"–66" (121.9 m–167.6 cm) chippers to go from square discharge to round blowpipe
- 10"–12" (25.4 cm–30.5 cm) round blowpipe straight pipe
- Hydraulic telescoping swivel discharge spout (requires auxiliary hydraulic power supply)
- Hydraulic hood opener includes cylinder and lugs; does not include hydraulic power supply to valve to operate same (Available for 75"+ (190.5 cm +) chippers)
- Manual swivel discharge spout (includes transition piece)
- 12" (30.5 cm) Black Blowpipe with 0.4" (0.95 cm) wall thickness bent 90 degrees; 48" high x 90" long (121.9 cm x 228.6 cm)
- "F" wheel assembly for 75" (190.5 cm) chippers includes hydraulic drive, forward and reverse controls for drive wheels and controls to raise and lower "F" wheel assembly (requires hydraulic power supply from another source); "F" wheel assembly for 83" (210.8 cm) chippers includes all of the above standard equipment
- 11.3' (3.4 m) long spout extension to load open top rail cars, complete with legs, down spout, sliding hood and components; requires hydraulic power supply from another source
- 4" (10.2 cm) thick chipper fronts
- Heavy-duty fan blades with inserts
- 5" (12.7 cm) thick chipper disc

MORBARKDEALERS.COM



MORBARK®



MORBARK® STATIONARY CHIPPER SPECIFICATIONS

GENERAL	US	METRIC
96" (243.8 CM) CHIPPER SPECIFICATIONS		
Capacity	30" or 27" roundwood	76.2 cm or 68.6 cm
Length	104"	2.6 m
Width	75"	1.9 m
Height	104.5"	2.6 m
Weight	30,000 lb	13608 kg
83" (210.8 CM) CHIPPER SPECIFICATIONS		
Capacity	27" roundwood	68.6 cm
Length	92"	2.3 m
Width	63"	1.6 m
Height	90"	2.3 m
Weight	19,000 lb	8618 kg
75" (190.5 CM) CHIPPER SPECIFICATIONS		
Capacity	22" roundwood	55.9 cm
Length	83"	2.1 m
Width	81"	2 m
Height	84"	2.1 m
Weight	15,600 lb	7076 kg
66" (167.6 CM) CHIPPER SPECIFICATIONS		
Capacity	18" roundwood	45.7 cm
Length	82"	2.1 m
Width	68"	1.7 m
Height	74.5"	1.9 m
Weight	11,000 lb	4990 kg
58" (147.3 CM) CHIPPER SPECIFICATIONS		
Capacity	15" roundwood	38.1 cm
Length	67"	1.7 m
Width	58"	1.5 m
Height	65"	1.6 m
Weight	8,200 lb	3719 kg
48" (121.9 CM) CHIPPER SPECIFICATIONS		
Capacity	11" roundwood	27.9 cm
Length	67"	1.7 m
Width	67"	1.7 m
Height	65"	1.6 m
Weight	8,200 lb	3719 kg

Specifications may vary with equipment options

Updated 3/11/2021

