

PS-8 STATIONARY POST PEELER PSP POLE AND POST PEELER

Optimal solutions for wood recycling!



STOEVELAAR



MORBARK®



MORBARK®

Stoevelaar Machinery is a versatile organisation with a broad product & service program for companies in the recycling industry and biomass.

Our assortment consists of premium recycling machines that make it possible to shred, chip, screen and sort all kind of recyclable material into a semi-finished or finished product.

Morbark based in the USA, has been innovating and manufacturing durable, high-performance equipment for more than 60 years. Stoevelaar Recycling is since 2017 successfully importer of Morbark Equipment for Europe. With its strong network of dealers Stoevelaar provides European custom made good quality machines and a superior customer service.

Please visit our website **www.stoevelaar-machinery.com** and find your local dealer or contact us directly by email **info@stoevelaar-machinery.com**

STOEVELAAR

Stoevelaar Machinery
Wolfveldseweg 1a
7737 PK Stegeren

T. +31 (0)529 408170
info@stoevelaar-machinery.com
www.stoevelaar-machinery.com

MORBARK PS8



OPTIONAL DISCHARGE FOR PS-8

- Bark Blower and Auger with 304 cm (10') blowpipe, for waste removal with drive. Total height machine with blower is 2,85 m
- Hydraulic powered outfeed roll

TECHNICAL SPECIFICATIONS*

PS-8 (BASE UNIT)

Capacity (diameter range)	7,6 cm – 30,5 cm
Capacity (length)	1,8 – 3,6 m
Power	Electrical
Production rate	12,2 m/min
Gross Weight	2,5 t
Length	3,70 m
Width	2,90 m folded / 4,50 m open
Height	2,1 m (2,85 m with blower)
Including	Hydraulic feed wheel drive Stationary infeed and outfeed wood rests
Options	Blower and auger Hydraulic powered outfeed roll

TECHNICAL SPECIFICATIONS

- Designed to debark material diameter 7,6 – 30,5 cm (3" to 12")
- Center section complete with debarking mechanism: split peeling head with a combination of
 - * carbide teeth (to remove bark and knots)
 - * planer knife cutterhead (to provide a smooth surface with only one pass though the machine)
- Hydraulic controlled infeed shoe
- Hydraulic top yoke assembly
- Support legs 99,06 cm (39") from bottom of leg to top of infeed.
- Motor base (to fit below electric motor) and V-belt drive
- Drive: Electric Motor 50-HP, 380 Volt, 50 Hz EU rated
- CE Specs



MORBARK PSP



PSP (WITH ROLLCASES)

7,6 – 30,5 cm

1,8 – 5,2 cm

Electrical

12,2 m/min

2,6 t (without roll cases)

8,10 m

4,80 m

2,30 m

Infeed 3,04 m (10')

Outfeed 3,04 m (10')

Infeed 6,08 m (20')

Outfeed 6,08 m (20')



INCLUDING:

- Infeed 3,04 m (10') rollcase with push arms and hydraulic drive.
- Outfeed 3,04 m (10') rollcase with 1 set of two-way kickers and hydraulic drive.

*All values are approx.